UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

ANCHORAGE (C-8) NE QUADRANGLE
ALASKA–MATANUSKA–SUSITNA BOROUGH
1:25 000-SCALE SERIES (TOPOGRAPHIC)
NE/4 ANCHORAGE (C-8) 1:63 360-SCALE QUADRANGLE

(ANCHORAGE D-8 1:63 360) (ANCHORAGE D-7 1:63 360) (ANCHORAGE C-8 SW) (ANCHORAGE C-8 NW) (ANCHORAGE C-7 NW) (ANCHORAGE C-7 SW) (ANCHORAGE C-8 SE)

149°48'45" 47'30" 45' 42'30" 40' 149°37'30" 61°45' 61°42'30" 61°40' 61°37'30"

352 000mE 353 354 355 R 3 W 358 359 40' 560 000 FEET 361 360 000mE

6849 000mN 6848 6847 6846 6845 6844 6843 6842 6841 6840 6839 6838 6837 6836 000mN

2 830 000 FEET

2 790 000 FEET

T 19 N T 18 N

TRACT A

Teakwood Lake

Deception Creek

Zero Lake

Bench Lake

Visnaw Lake

HOUSTON CORPORATE BOUNDARY

TRAIL WINTER TRAIL WINTER TRAIL WINTER TRAIL WINTER TRAIL WINTER TRAIL WINTER TRAIL

WILLOW 19 KM WASILLA 24 KM

Houston GEORGE PARKS Gravel Pit City Hall ARMSTRONG ROAD Little Susitna River Campground MSB GPS 10 Boat Ramp Well Gaging Sta BM 78.4 Gravel Pit Gravel Pit Gravel Pit Landing Strip SILVER DRIVE MSB GPS 20

SUSITNA RIVER LITTLE SUSITNA RIVER

R 3 W R 2 W

Produced by the United States Geological Survey

Control by USGS and NOS/NOAA

Compiled from aerial photographs taken 1972. Revisions shown in purple and woodland compiled from aerial photographs taken 1988 and other sources and have been field checked
Map edited 1993. Conflicts may exist between some updated features and previously mapped contours

1927 North American Datum (NAD 27). Projection and blue 1000-meter ticks: Universal Transverse Mercator, zone 6
10 000-foot ticks: Alaska Coordinate System, zone 4

North American Datum of 1983 (NAD 83) is shown by dashed corner ticks. The values of the shift between NAD 27 and NAD 83 for 7.5-minute intersections are given in USGS Bulletin 1875

Land lines are omitted in areas of extensive tract surveys

Swamps, as portrayed, indicate only wetter areas, usually of low relief, as interpreted from aerial photographs

GN MN 2°24' 43 MILS 24½° 436 MILS

UTM GRID AND 1993 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

SCALE 1:25 000

1 0 1 2 KILOMETERS
½ 0 1 MILE
1000 0 5000 FEET

CONTOUR INTERVAL 10 METERS
DOTTED LINES REPRESENT 5-METER CONTOURS
NATIONAL GEODETIC VERTICAL DATUM OF 1929

CONTROL ELEVATIONS SHOWN TO THE NEAREST 0.1 METER
OTHER ELEVATIONS SHOWN TO THE NEAREST METER
To convert meters to feet multiply by 3.2808
To convert feet to meters multiply by .3048

COMPLIES WITH U.S. GEOLOGICAL SURVEY STANDARDS FOR SPATIAL ACCURACY–CLASS 2

FOR SALE BY U.S. GEOLOGICAL SURVEY
FAIRBANKS, ALASKA 99701; DENVER, COLORADO 80225; OR RESTON, VIRGINIA 22092
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

ALASKA
QUADRANGLE LOCATION

CONTOURS AND ELEVATIONS IN METERS

ROAD CLASSIFICATION

Primary highway, hard surface
Secondary highway, hard surface
Light-duty road, hard or improved surface
Unimproved road
State Route

ANCHORAGE (C-8) NE, ALASKA
NE/4 ANCHORAGE (C-8) 1:63 360-SCALE QUADRANGLE
61149-F6-TM-025

1979
REVISED 1993

INTERIOR-GEOLOGICAL SURVEY RESTON, VIRGINIA-1993